



Product Attributes		Select All
<b>Categories</b>	<a href="#">Connectors, Interconnects</a> <a href="#">FFC, FPC (Flat Flexible) Connectors</a>	<input checked="" type="radio"/>
<b>Manufacturer</b>	Molex	<input type="checkbox"/>
<b>Series</b>	<a href="#">Easy-On 52435</a>	<input type="checkbox"/>
<b>Packaging</b> 	Cut Tape (CT) 	<input type="checkbox"/>
<b>Part Status</b>	Active	<input type="checkbox"/>
<b>Flat Flex Type</b>	FFC, FPC	<input type="checkbox"/>
<b>Mounting Type</b>	Surface Mount, Right Angle	<input type="checkbox"/>
<b>Connector/Contact Type</b>	Contacts, Top	<input type="checkbox"/>
<b>Number of Positions</b>	24	<input type="checkbox"/>
<b>Pitch</b>	0.020" (0.50mm)	<input type="checkbox"/>
<b>Termination</b>	Solder	<input type="checkbox"/>
<b>FFC, FCB Thickness</b>	0.30mm	<input type="checkbox"/>
<b>Height Above Board</b>	0.079" (2.00mm)	<input type="checkbox"/>
<b>Locking Feature</b>	Slide Lock	<input type="checkbox"/>
<b>Cable End Type</b>	Straight, Tapered	<input type="checkbox"/>
<b>Contact Material</b>	Phosphor Bronze	<input type="checkbox"/>
<b>Contact Finish</b>	Gold	<input type="checkbox"/>
<b>Housing Material</b>	Polyamide (PA46), Nylon 4/6	<input type="checkbox"/>
<b>Actuator Material</b>	Polyphenylene Sulfide (PPS)	<input type="checkbox"/>
<b>Features</b>	Solder Retention, Zero Insertion Force (ZIF)	<input type="checkbox"/>
<b>Voltage Rating</b>	50V	<input type="checkbox"/>
<b>Operating Temperature</b>	-40°C ~ 85°C	<input type="checkbox"/>
<b>Material Flammability Rating</b>	UL94 V-0	<input type="checkbox"/>
<b>Current Rating (Amps)</b>	0.5A	<input type="checkbox"/>
<b>Contact Finish Thickness</b>	-	<input type="checkbox"/>
<b>Housing Color</b>	-	<input type="checkbox"/>
<b>Actuator Color</b>	-	<input type="checkbox"/>
<b>Mating Cycles</b>	20	<input type="checkbox"/>